



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.



ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-01	1	FRAME TOP	6061		2
			-03	1	FRAME BOTTOM	6061		3
			-05	1	FLAT SCISSOR BAR	6061		4
			-07	1	BENT SCISSOR BAR	6061		5
			-09	1	STANDOFF	304 S.S.		6
			-11	1	CENTER BRACE	6061		7
			-13	1	GAGE PLATE	6061		8
			-15	1	SPRING PIN	6061		9
			-17	2	CLAMP PAD	WHITE DELRIN		10
			-19	1	STOP	WHITE DELRIN		11
			-21	2	PAD	BLACK RUBBER		12
			-23	1	PHILLIPS RND HEAD SCREW	S.S.	10-32 UNF -2A X 1 (MCMASTER-CARR #91773A833) MODIFIED	13
		B/O	-25	5	FLAT WASHER	STEEL	#10 (MCMASTER-CARR #98032A469)	1
		B/O	-27	2	HEX NUT	STEEL	#10-32 UNF -2B (MCMASTER-CARR #90480A195)	1
		B/O	-29	4	PHILLIPS RND HEAD SCREW	STEEL	#8-32 UNC -2A X 1-1/4 (MCMASTER-CARR #90279A201)	1
		B/O	-31	4	PHILLIPS FLAT HEAD SCREW	STEEL	#8-32 UNC -2A X 3/8 (MCMASTRE-CARR #90273A192)	1
		B/O	-33	2	PHILLIPS FLAT HEAD SCREW	STEEL	#8-32 UNC -2A X 3/4 (MCMASTER-CARR #90273A197)	1
		B/O	-35	2	PHILLIPS PAN HEAD SCREW	STEEL	#10-32 UNF -2A X 5/8 (MCMASTER-CARR #90272A830)	1
		B/O	-37	2	SPRING	S.S.	Ø.048 x Ø3/8 X 5.05 EXT LG. (MCMASTER-CARR #94135K23)	1
		B/O	-39	2	FLAT WASHER	STEEL	#8 (MCMASTER-CARR #98023A113)	1

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		ADDED NOTE 1 TO SHEET 1. -01 & -03 CH'D DIMS WAS .409 IS .402. WAS 4.849 IS 4.775. CH'D FINISH WAS POWDER COAT FORREST T-5920 S9 YELLOW RIBBON MIL-P-83348 IS POWDER COAT YELLOW FED #13538. -03 CH'D NOTE WAS ENGRAVE TOOL NO. SERIAL NO.. AND MADE IN USA TO FIT IS ENGRAVE T/N, S/N, MADE IN USA. -05 & -07 CH'D DIM WAS Ø.170 THRU Ø.288 IS Ø.200 Ø.31 X 82°. -11 CH'D HOLE CALLOUTS DIM WAS Ø.170 THRU Ø.288 IS Ø.200 Ø.31 X 82°. WAS .079 FAR SIDE Ø.171 IS Ø.08 FAR SIDE .17 X 82°. WAS .076 IS .08. WAS .078 IS .08. -13 CH'D DIM WAS 3.341 IS (3.341). -19 ADDED MISSING DIM 3X R.12. -23, -25, -27, -29, -31, -33, -35 ADDED P/N'S TO BOM.	2/13/14	DPD	GE
2	15-0117	-01 & -03 ADDED .10 X 45° CHAMFER. CH'D FINISH WAS POWDER COAT YELLOW FED #13538 IS RED ANODIZE. -05 & -07 CH'D HOLE CALL OUTS WAS Ø.188 IS Ø.196 THRU, WAS Ø.200 Ø.31 X 82° IS Ø.177 Ø.31 X 82°. -09 CH'D THRU HOLE DIM'S WAS Ø.190 IS Ø.196. WAS Ø.277 IS LIMIT Ø.2770-.2768. -11 CH'D DIMS WAS Ø.288 S.F. -09 IS LIMIT Ø.2776-.2772. WAS 2X Ø.200 Ø.31 X 82° IS Ø.177 Ø.31 X 82°. -13 CH'D HOLE CALL OUTS WAS Ø.188 IS Ø.196 THRU. -25 CH'D B/O WAS MCMASTER-CARR #90126A514 IS #98032A469, ADDED TWO BETWEEN -13 AND -01 & -03.	5/29/2015	RJC	JAG




NOTES

- APPLY LOCTITE 242 FROM BACKSIDE, ENSURING ASSY. ROTATES FREELY.
- USE APPROPRIATE ADHESIVE TO ASSEMBLE -21 TO -01 AND -21 TO -03.

DART AEROSPACE			
TITLE M/R BLADE TRIM TAB GUAGE			
DWG NO. RBW109-3101-14-1			REV 2
MAT'L UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1		DRAWN BY: PERRITT APPROVED TREAT FINISH SPEC	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R		USED ON MODEL	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING		AGUSTA	
SCALE 1:3	DATE 3/8/2010	SHEET 1 OF 13	


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-01 CH'D DIMS WAS .409 IS .402, WAS 4.849 IS 4.775, CH'D FINISH WAS POWDER COAT FORREST T-5920 S9 YELLOW RIBBON MIL-P-83348 IS POWDER COAT YELLOW FED #13538.	2/13/14	DPD	GE
2	15-0117	-01 ADDED .10 X 45° CHAMFER, CH'D FINISH WAS POWDER COAT YELLOW FED #13538 IS RED ANODIZE.	5/29/2015	RJC	JAG





DART AEROSPACE			
TITLE M/R BLADE TRIM TAB GUAGE			
DWG NO. RBW109-3101-14-1-01			REV 2
MAT'L 6061		DRAWN BY: PERRITT	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		APPROVED D Weil	
.XXX ± .005		TREAT FINISH	
.XX ± .01		RED ANODIZE	
.X ± .1		SPEC MIL-A-8625F, TYPE II, CLASS II	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R		USED ON MODEL AGUSTA	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING			
SCALE 2:3	DATE 3/8/2010	SHEET 2 OF 13	

REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-03 CH'D DIMS WAS .409 IS .402, WAS 4.849 IS 4.775, CH'D NOTE WAS ENGRAVE TOOL NO. SERIAL NO., AND MADE IN USA TO FIT IS ENGRAVE T/N, S/N, MADE IN USA, CH'D FINISH WAS POWDER COAT FORREST T-5920 S9 YELLOW RIBBON MIL-P-83348 IS POWDER COAT YELLOW FED #13538.	2/14/2014	DPD	GE
2	15-0117	-03 ADDED .10 X 45° CHAMFER, CH'D FINISH WAS POWDER COAT YELLOW FED #13538 IS RED ANODIZE.	5/29/2015	RJC	JAG



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-05 CH'D DIM WAS Ø.170 THRU ✓ Ø.288 IS Ø.200 ✓ Ø.31 X 82°.	2/13/2014	DPD	GE
2	15-0117	-05 CH'D HOLE CALL OUTS WAS Ø.188 IS Ø.196 THRU, WAS Ø.200 ✓ Ø.31 X 82° IS Ø.177 ✓ Ø.31	5/29/2015	RJC	JAG






(-05)

FLAT SCISSOR BAR

DART AEROSPACE	
TITLE M/R BLADE TRIM TAB GUAGE	
DWG NO. RBW109-3101-14-1-05	REV 2
MAT'L 6061	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005 FRACTIONS ± 1/8	HEAT TREAT
.XX ± .01 ANGLES ± 5°	FINISH CLEAR ANODIZE
.X ± .1	SPEC MIL-A-8625F, TYPE II, CLASS I
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	USED ON MODEL
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	AGUSTA
SCALE 2:1	DATE 3/8/2010
SHEET 4 OF 13	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-07 CH'D HOLE CALLOUTS DIM WAS Ø.170 THRU ✓ Ø.288 IS Ø.200 ✓ Ø.31 X 82°.	2/13/2014	DPD	GE
2	15-0117	-07 CH'D HOLE CALL OUTS WAS Ø.188 IS Ø.196 THRU, WAS Ø.200 ✓ Ø.31 X 82° IS Ø.177 ✓ Ø.31 X 82°.	5/29/2015	RJC	JAG






(-07)

BENT SCISSOR BAR

DART AEROSPACE	
TITLE M/R BLADE TRIM TAB GUAGE	
DWG NO. RBW109-3101-14-1-07	REV 2
MAT'L 6061	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005 FRACTIONS ± 1/8	HEAT TREAT
.XX ± .01 ANGLES ± .5°	FINISH CLEAR ANODIZE
.X ± .1	SPEC MIL-A-8625F, TYPE II, CLASS I
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	USED ON MODEL
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	AGUSTA
SCALE 2:1	DATE 3/8/2010
SHEET 5 OF 13	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	15-0117	-09 CH'D THRU HOLE DIM'S WAS Ø.190 IS Ø.196, WAS Ø.277 IS LIMIT Ø.2770-.2768.	5/29/2015	RJC	JAG







(-09)

STANDOFF

DART AEROSPACE	
TITLE M/R BLADE TRIM TAB GAUGE	
DWG NO. RBW109-3101-14-1-09	REV 2
MAT'L 304 S.S.	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005 FRACTIONS ± 1/8	HEAT
.XX ± .01 ANGLES ± 5°	TREAT
.X ± .1	FINISH
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	SPEC
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	USED ON MODEL
	AGUSTA
SCALE 2:1	DATE 3/8/2010
	SHEET 6 OF 13

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-11 CH'D HOLE CALLOUTS DIM WAS \varnothing .170 THRU \varnothing .288 IS \varnothing .200 \varnothing .31 X 82°, WAS .079 FAR SIDE \varnothing .171 IS \varnothing .08 FAR SIDE \varnothing .17 X 82°, WAS .076 IS .08, WAS .078 IS .08.	2/13/2014	DPD	GE
2	15-0017	-11 CH'D DIMS WAS \varnothing .288 S.F. -.09 IS LIMIT \varnothing .2776-.2772, WAS 2X \varnothing .200 \varnothing .31 X 82° IS \varnothing .177 \varnothing .31 X 82°.	5/29/2015	RJC	JAG



(-11)


CENTER BRACE



TITLE M/R BLADE TRIM TAB GUAGE		
DWG NO. RBW109-3101-14-1-11	REV 2	
MAT'L 6061	DRAWN BY: PERRITT	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>	
.XXX ± .005	HEAT TREAT	
.XX ± .01	FINISH CLEAR ANODIZE	
.X ± .1	SPEC MIL-A-8625F, TYPE II, CLASS I	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	USED ON MODEL	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	AGUSTA	
SCALE 2:1	DATE 3/8/2010	SHEET 7 OF 13

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.




REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-13 CH'D DIM WAS 3.341 IS (3.341).	2/13/2014	DPD	GE
2	15-0117	-13 CH'D HOLE CALL OUTS WAS Ø.188 IS Ø.196 THRU	5/29/2015	RJC	JAG



DART AEROSPACE			
TITLE M/R BLADE TRIM TAB GUAGE			
DWG NO. RBW109-3101-14-1-13			REV 2
MAT'L 6061		DRAWN BY: PERRITT	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		APPROVED <i>D Well</i>	
.XXX ± .005		TREAT	
.XX ± .01		FINISH	
.X ± .1		CLEAR ANODIZE	
1. BREAK ALL SHARP EDGES .015 x 45°		SPEC MIL-A-8625F, TYPE II, CLASS I	
OR .015R		USED ON MODEL	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING		AGUSTA	
SCALE 1:1	DATE 3/8/2010	SHEET 8 OF 13	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED





-15

SPRING PIN



DART AEROSPACE	
TITLE M/R BLADE TRIM TAB GUAGE	
DWG NO. RBW109-3101-14-1-15	REV 2
MAT'L 6061	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005	HEAT TREAT
.XX ± .01	FINISH
.X ± .1	CLEAR ANODIZE
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	SPEC MIL-A-8625F, TYPE II, CLASS I
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	USED ON MODEL
	AGUSTA
SCALE 2:1	DATE 3/8/2010
	SHEET 9 OF 13

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL



2X 8-32 UNC - 2B
THRU ALL






(-17)
CLAMP PAD

DART AEROSPACE	
TITLE M/R BLADE TRIM TAB GAUGE	
DWG NO. RBW109-3101-14-1-17	REV 2
MAT'L WHITE DELRIN	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005 FRACTIONS ± 1/8	HEAT TREAT
.XX ± .01 ANGLES ± 5°	FINISH
.X ± .1	SPEC
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	USED ON MODEL
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	AGUSTA
SCALE 2:1	DATE 3/8/2010
SHEET 10 OF 13	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-19 ADDED MISING DIM 3X R.12.	2/13/2014	DPD	GE







-19

STOP

DART AEROSPACE	
TITLE M/R BLADE TRIM TAB GUAGE	
DWG NO. RBW109-3101-14-1-19	REV 2
MAT'L WHITE DELRIN	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005	HEAT
.XX ± .01	TREAT
.X ± .1	FINISH
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	SPEC
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	USED ON MODEL
SCALE 2:1	AGUSTA
DATE 3/8/2010	SHEET 11 OF 13

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED




(-21)

PAD

DART AEROSPACE	
TITLE M/R BLADE TRIM TAB GAUGE	
DWG NO. RBW109-3101-14-1-21	REV 2
MAT'L BLACK RUBBER	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005 FRACTIONS ± 1/8	HEAT
.XX ± .01 ANGLES ± 5°	TREAT
.X ± .1	FINISH
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	SPEC
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	USED ON MODEL
	AGUSTA
SCALE 2:1	DATE 3/8/2010
	SHEET 12 OF 13

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED



PHILLIPS RND HEAD SCREW

(-23)

DART AEROSPACE	
TITLE M/R BLADE TRIM TAB GAUGE	
DWG NO. RBW109-3101-14-1-23	REV 2
MAT'L S.S.	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005	HEAT
.XX ± .01	TREAT
.X ± .1	FINISH
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	SPEC
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	USED ON MODEL
	AGUSTA
SCALE 2:1	DATE 3/8/2010
	SHEET 13 OF 13